argo

improve your life

HEATING, AIR & WELLNESS CATALOGUE 2011/2012

Contents

Fan heaters and multi-functional devices page 3

Electric convector heaters, mineral oil-filled electric radiators, radiant panel heaters, halogen and quartz heaters page 7

Gas heaters and radiators page 11

Pellet and wood-burning stoves page 13

Air treatment page 15

Electric blankets, pillows and footwarmers page 19

Essential oil diffusers, mist lamps pure essential oil vaporisers page 21

Technical specifications page 23

Fan heaters

Ceramic fan heaters

HIFAN hifi

- Hi-tech design, dolby surround type casing, silver/glossy black finish
- Extremely quiet
- Digital display, LED symbols and “soft touch” controls
- Slim remote control with an operating range of up to 6 m
- Automatic oscillation for optimal air diffusion in the room
- Programmable timer (0 - 12 hours)
- Adjustable room temperature (5 - 35°C)
- Pollen filter, easily removed for cleaning purposes
- Dual electronic protection against overheating
- Overturn protection device

Dimensions: 1018x290x290 mm

W 1500/2500

Ceramic fan heater
This is fitted with a ceramic PTC heating element, which heats up very quickly and has built-in protection against current overload and overheating. The PTC (Positive Temperature Coefficient) is a polycrystalline ceramic barium titanate semiconductor. The real advantage of using it is its ability to self-regulate in terms of heat, in fact the heating element resistance increases sharply when a specific temperature is reached (Tmax). Thanks to this special feature (resistance variation in accordance with the temperature), which saves a significant amount of energy, temperature regulation is no longer necessary, and no additional external safety systems monitoring overheating are required.

Traditional fan heater
Featuring a wire-wound heating element, this is still equipped with overheating prevention safety devices and, where necessary, overturn protection devices.

Multi-functional fan heater
Besides HEATING by means of the ceramic PTC heating element, it HUMIDIFIES, PURIFIES AIR thanks to the multi-layer filter and IONISES.

Ceramic fan heaters

HI FAN tower

- Hi-tech design, with very elegant black glass base
- Extremely quiet, thanks to its 3 AC compact fans
- Large digital display, white LED symbols and “soft touch” controls
- Ultra-thin
- Automatic oscillation for optimal air diffusion in the room
- Programmable timer (0 - 7.5 hours)
- Multi-functional remote control with an operating range of up to 6 m
- Pollen filter, easily removed for cleaning purposes
- Made from self-extinguishing and impact-resistant plastic
- Dual electronic protection against overheating
- Overturn protection device

Dimensions: 788x263x263 mm

W 1300/2500

HI FAN black mini

- Extremely quiet AC compact fan
- Air pollen filter, can be removed for cleaning
- Made from self-extinguishing and impact-resistant plastic
- Metal front grille and hi-gloss silver finish frame
- For use as a floor-standing model or placed on shelves
- Dual electronic protection against overheating

Dimensions: 170x200x94 mm

W 800/1200

HI FAN black swing

- Sturdy and easy to handle, with a modern design
- Can be floor-standing or placed on a desk or shelf
- Cool ventilation
- Room thermostat
- 2 angle options to direct the air flow as required
- Dual electronic protection against overheating

Dimensions: 250x250x130 mm

W 1000/1800

HI FAN black

- Hi-tech design and functions
- Can be floor-standing, placed on a shelf or wall-mounted, thanks to the special articulated mount
- When wall-mounted for use as a split flat, it can be directed downwards, to the right or to the left and has IP21 specifications (use in bathrooms)
- Extremely quiet, thanks to its 2 special AC compact fans
- Large digital display, red LED symbols and “soft touch” controls
- Slim remote control with an operating range of up to 6 m
- Ultra-thin: just 8 cm deep
- Programmable timer (0 - 12 hours)
- Adjustable room temperature (5 - 35°C)
- Air pollen filter, easily removed for cleaning purposes
- Made from self-extinguishing and impact-resistant plastic
- Dual electronic protection against overheating
- Overturn protection device

Dimensions: 180x440x80 mm

W 1300/2000

HI FAN

- Made from self-extinguishing hi-gloss white plastic
- Summertime ventilation
- Metal front grille and hi-gloss silver finish frame
- Overheating safety device
- Dual electrical insulation
- Overturn safety device
- IP21 protection (which means the fan heater can also be used in the bathroom)

HI FAN Classic
- Manual control panel
- Manual 60° rotation, with concealed rotating base
- Very quiet AC compact fan

HI FAN Digit and Digit Plus
- Digital control panel and liquid crystal display
- Timer from 1 to 24 h
- Automatic 60° rotation, with concealed rotating base
- Argo DPM (dynamic power management) system for optimised power regulation and energy consumption
- Rubber buttons and blue backlit display
- Very quiet tangential fan (Hi Fan Digit Plus)
- Infrared remote control (Hi Fan Digit Plus)

CLASSIC

DIGIT

Dimensions: 250x190x155 mm (Classic and Digit)

Dimensions: 380x180x160 mm (Digit Plus)

W 900/1800

DIGIT PLUS

Wall-mounted ceramic fan heaters

SPLITTO

- Digital control panel
- Light-up LCD display and soft touch buttons
- Infrared remote control
- Option of adjusting temperatures between 15° and 35°C
- Automatic air flow direction
- Programmable timer (1 - 8 hours)
- Made from self-extinguishing and impact-resistant plastic with hi-gloss silver finish
- Overheating safety device
- Built-in ioniser

Dimensions: 125x545x215 mm

W 1000/2000

SPLITTO JR

- Equipped with an extremely quiet tangential fan
- Manually controlled power
- Made from self-extinguishing and impact-resistant pearl white plastic
- Protective grille in heat-resistant plastic
- Flap with automatic oscillation
- Overheating safety device

Dimensions: 200x500x140 mm

W 1000/2000

Multi-functional ceramic fan heater

QUADRO

4 IN 1
- Fan heater with ceramic PTC heating element
- Evaporating humidifier
- Ioniser
- Air purifier

- Extremely quiet radial fan
- Electronic temperature and timer control
- Humidity control with electronic hygrometer
- Five power settings from 600 to 2000 watts
  Some are activated automatically and others can be selected from the control panel in heating mode (1200/2000 watts)
- Air purification with pollen filter
- Activated charcoal filter and natural fibre filter with thermostatic properties
- Made from self-extinguishing and impact-resistant plastic with hi-gloss black finish

Dimensions: 430x450x175 mm

W 1000/2000

Fan heater with wire-wound heating element

ALIENO

- Extremely simple
- Wire-wound heating element
- Thermostat adjustment knob
- Selector knob for:
  - cool ventilation
  - warm ventilation (1000 watts)
  - very warm ventilation (2000 watts)
- Practical carry handle
- Dual electronic protection against overheating
- Overturn protection device
- For use as a floor-standing model or placed on shelves

Dimensions: 250x200x190 mm

W 1000/2000

ASTRO

- Stylised design
- Wire-wound heating element
- Knob for thermostat adjustment with anti-freeze function
- Selector for:
  - cool ventilation
  - warm ventilation (1000 watts)
  - very warm ventilation (2000 watts)
- Made from self-extinguishing and impact-resistant plastic
- Available in two colours: white and orange
- For use as a floor-standing model or placed on shelves

Dimensions: 221x222x151 mm

W 1000/2000

WHITE

ORANGE

UFO

- New and unusual design
- Wire-wound heating element
- Elegant guide light at the rear to indicate operation
- Conical selector knob for:
  - cool ventilation
  - warm ventilation (1500 W)
- Made from self-extinguishing and impact-resistant plastic
- Available in two colours: white and violet
- For use as a floor-standing model or placed on shelves

Dimensions:∅ 215X185 mm

W 1500

WHITE

VIOLET

Electric convector heaters
Mineral oil-filled electric radiators
Radiant panel heaters
Halogen and quartz heaters

improve your life

Electric convector heaters

HI FLOOR DESIGN

HI FLOOR DESIGN PLUS

- Innovative design in a console style
- Extremely light and easy to use
- 3 power settings: 750/1250/2000 W
- Room thermostat for temperature regulation
- Two versions: Design and Design Plus
- Both have a powerful fan (Turbo function)
- The Design Plus version also has a 24 h timer
- Air discharge at the front and at the top
- Side carry handles (Turbo mode)
- Overheating safety device

Dimensions: 450x693x190 mm

W 750/1250/2000

TURBO

TIMER

Design Plus only

Electric convector heater
Fitted with a wire-wound heating element, this diffuses heat by convection and, thanks to the supplementary Turbo function, also by means of forced ventilation.

Mica radiant panel
Features a Mica heating element; this consists of ultra-thin sheets or strips of Mica, around which resistor elements are positioned. These elements heat up and exploit the electrical insulation potential of the Mica.
Its long lifespan is guaranteed for two main reasons:
- it is not susceptible to attacks by chemical agents;
- performance and physical features remain consistent and uniform over time and after the repeated heating cycles to which the system is subjected.

Mineral oil-filled electric radiators
Natural and quiet heating through the circulation of electrically heated diathermic mineral oil.

Quartz heater
Quartz bulbs radiate heat.

Halogen heater
Halogen bulbs radiate heat.

Electric convector heaters

HI-FLOOR JUNIOR

- Slim design
- Extremely light and functional, ideal for homes and offices
- 3 power settings: 750/1250/2000 W
- Room thermostat for temperature regulation
- Integrated turbo function for maximum instantaneous heat
- Front and rear air discharge
- Side carry handles
- Overheating safety device

Dimensions: 485x690x200 mm

W 750/1250/2000

TURBO

HI-FLOOR classic

HI-FLOOR classic T

- Traditional design
- Two versions: classic (Turbo) and classic T (Turbo Timer)
- Two power settings: 1000/2000 W
- Thermostat knob
- Turbo function with axial fan
- Timer (classic T version only)
- Ideal for floor-standing use
- Also equipped with special mounts for fixed wall installation

Dimensions: 425x625x215 mm

W 1000/2000

TURBO

TIMER

classic T only

Pepper 7 - 9 - 11

- Innovative line of mineral oil-filled electric radiators
- The heat is distributed by natural convection and radiation from 7, 9 or 11 elements
- 16 mm wide heating elements with special profiles enhancing convection
- Three adjustable power settings:
  - Pepper 7: 600/900/1500 watts
  - Pepper 9: 800/1200/2000 watts
  - Pepper 11: 1000/1500/2500 watts
- Overturn and overheating protection device
- Compliant with the most stringent European safety standards

Dimensions: 630x380x160 mm (Pepper 7)

W 600/900/1500

Dimensions: 630x470x160 mm (Pepper 9)

W 800/1200/2000

Dimensions: 630x540x160 mm (Pepper 11)

W 1000/1500/2500

Chily 7 - 9 - 11

- Traditional line of mineral oil-filled electric radiators
- The heat is distributed by natural convection and radiation from 7, 9 or 11 heating elements
- Room thermostat
- Overturn and overheating protection device
- Compliant with the most stringent European safety standards

Dimensions: 642x346x125 mm (Chily 7)

W 900/1500

Dimensions: 642x426x125 mm (Chily 9)

W 900/1500

Dimensions: 642x506x125 mm (Chily 11)

W 1200/2000

Radiant panel heater

HI FLOOR ray

- Optimal heat radiation and limited energy consumption
- Mica heating element
- Slim design with metal front grille
- Three power control settings: 500/1000/1500 W
- Room thermostat
- Easy to move
- Ideal for floor-standing use
- Also equipped with special mounts for fixed wall installation

Dimensions: 455x780x240 mm

Dimensions: 455x780x80 mm (without mounts)

W 500/1000/1500

Halogen and quartz heaters

CREOLA Q3

- Electric heater with 3 quartz bulbs
- Small and efficient
- Three heat output levels, up to 1500 watts
- Metal protective grille
- Overheating safety devices
- Device triggering automatic shut-down in the event of overturning

Dimensions: 210x410x183 mm

W 500/1000/1500

CALDOFAI 1200 GR

- Electric heater with 3 halogen bulbs
- Three heat output levels, up to 1200 W
- Wide range of automatic or manual rotation
- Heat diffuser with honeycomb structure
- Metal protective grille
- Rear carry handle
- Overheating safety device
- Device triggering automatic shut-down in the event of overturning

Dimensions: 550x400x300mm

W 400/800/1200

CALORELLA 1200 S

- Traditional halogen electric heater
- Three heat output levels, up to 1200 watts
- Wide range of automatic or manual rotation
- Heat diffuser with honeycomb structure
- Metal protective grille
- Rear carry handle
- Overheating safety device
- Device triggering automatic shut-down in the event of overturning

Dimensions: 500x310x225 mm

W 400/800/1200

Gas heaters and radiators

Catalytic heater

44RQ

- Heater with certified catalytic panel compliant with European standards
- Wide range heat diffusion thanks to the Argo patented special catalytic panel
- Large compartment for housing the LPG cylinder
- A pressure regulator and high quality gas pipe for connection to the cylinder are supplied with the heater
- Ultra-thick sheet metal, treated against rust and finished with special painting powders to prevent ageing
- Piezoelectric ignition and heat regulation using a single knob

Dimensions: 805x425x445 mm

W 2270/2600/3050

Infrared heater

INFRA 42C

- Traditionally-designed infrared heater, suitable for any environment
- Piezoelectric ignition
- Three heat output levels, from 1.4 kW (min.) to 4.0 kW (max.)
- An IMQ-certified pressure regulator and high quality gas pipe conforming to national regulations for connection to LPG cylinders are supplied with the heater
- Rear compartment housing a cylinder (up to 10 kg)
- Swivelling wheels equipped with a wheel lock
- Triple safety device: ODS, which shuts down the heater if the percentage of oxygen in the room exceeds permitted levels; PF, which automatically stops the gas supply if the pilot flame is extinguished; knock/overturn protection which automatically stops the gas supply if the appliance is knocked or at risk of overturning

Dimensions: 740x420x360 mm

W 1200/2800/4000

Gas heaters

VENTOSOLE

246

Dimensions:
760x720x250 mm

W 10300

316

Dimensions:
695x830x270 mm

W 11000

VENTOSOLE
THERMOSOLE

- Ventosole and Thermosole are gas heaters for fixed installation with the expulsion of combustion fumes via chimney
- Available in various models with different heat outputs, with or without forced ventilation, and with piezoelectric or electronic ignition
- Suitable for methane or LPG (optional), with a traditional enamel finish
- All Argo heaters provide solutions for applications with a heat output ranging from 5000 to 11000 W
- Argo heaters are the first choice for all situations where large heat outputs are required in buildings that cannot be fully modernised

THERMOSOLE

1.62

Dimensions:
580x440x240 mm

W 6500

2.78

Dimensions:
645x600x240 mm

W 8450

2.98

Dimensions:
710x660x240 mm

W 9200

Balanced flow gas radiators

LYRA 3000/4000

- Balanced flow radiator for primary heating installations
- Suitable for LPG or methane fuel supply
- Cast-iron sealed-chamber burner
- Warm air flow diffused by natural convection and forced ventilation (in VTQ models)
- Available in three versions:
  - Lyra 3000SQ: 3060 watts
  - Lyra 3000VTQ: 3060 watts (ventilated)
  - Lyra 4000VTQ: 4000 watts (ventilated)
- Very quiet tangential fan
- Piezoelectric ignition and heat regulation
- The ideal solution for installing completely safe, fixed and autonomous heating systems in historic buildings, rural areas, etc...

Dimensions: 490x590x205 mm (Lyra 3000)

W 3060

Dimensions: 490x710x205 mm (Lyra 4000)

W 4000

Pellet and wood-burning stoves

Pellet stoves

LCD display

bruciapellet

- Bruciapellet 65 is the smallest stove in a range of Argo products designed for the renewable energy source of wood pellets
- Bruciapellet 80 and 110, a modular heating model able to provide a maximum heat output of 8 or 11 kW, completes the range

- Efficiency at maximum power:
  Bruciapellet 65: 86%.
  Bruciapellet 80: 88.5%.
  Bruciapellet 110: 82%.

- Nominal heat output:
  Bruciapellet 65: 6 kW.
  Bruciapellet 80: 8 kW.
  Bruciapellet 110: 11 kW.

- Reduced heat output:
  Bruciapellet 65: 3.5 kW.
  Bruciapellet 80/110: 4.3 kW.

- Stainless steel burner ideal for large temperature variations
- Modern look without visible bolts on the top and front plates
- Single steel door with ceramic glass and concealed handle
- Load capacity of approximately 13.5 (65) or 15 kg (80-110)
- Elegant finish using high quality enamel painting powders
- Certified by IMQ and compliant with EN14785-2006 standards

Dimensions: 930x460x510 mm (65)

W 7200

Dimensions: 1040x520x550 mm (80)

W 9400

Dimensions: 1040x520x550 mm (110)

W 13900

GREY
GREEN

GREY
GREEN

MIGNON SL

SUPER SL

- The famous multi-fuel Argo stoves, which have been evolving since the first design in 1953, demonstrate the durability and reliability of Argo products
- The Super and Mignon stoves are modern, compliant with current standards and eligible for tax deduction initiatives
- Efficiency consistently higher than 70% guarantees maximum-efficiency heat when burning wood, a renewable energy source
- The cast iron lid has handy removable rings that can be used for cooking, just as they were in the past
- The combustion chamber is made from refractory bricks
- The ash compartment is easily accessible at the front of the stoves
- Traditional enamel finish
- Available in two elegant colours that will never go out of fashion and adapt easily to any environment

Dimensions: 740x320x320 mm (Mignon SL) **W 6000**

Dimensions: 860x380x380 mm (Super SC) **W 8000**

improve your life

Dehumidifiers

POWERDRY 13 - 17

- Innovative, compact and linear design
- 13 and 17 litres/day (32°C – 80%R.H.)
- 5 humidity level settings from 20% to 80%
- 3 coloured LEDs indicate operating status
- Extremely quiet
- Condensation collection reservoir at the rear
- Hydraulic connection for continuous condensation drainage
- Environmentally friendly refrigerant R134a

Dimensions: 490x365x215 mm

NARCIS BABY 10

- Dehumidifier 10 litres/day
- Modern styling, made from pearl white hi-gloss ABS
- Quiet and functional, with humidistat and LED guide light with three different colours depending on operating status
- Condensation collection reservoir at the rear
- Hydraulic connection for continuous condensation drainage
- Rotary compressor
- Environmentally friendly refrigerant R134a

Dimensions: 435x321x258 mm

narcis
12 - 16 - 20 - 24

- 12, 16, 20 and 24 litres/day dehumidifiers
- Modern styling, made from pearl white hi-gloss ABS
- Quiet and functional, with humidistat and three LEDs displaying operating status
- Condensation collection reservoir at the front with transparent window for viewing condensation level
- Hydraulic connection for continuous condensation drainage
- Rotary compressor
- Environmentally friendly refrigerant R410A (R134a for the 12 l model)

Dimensions: 632x405x291 mm

ecodry pro 50
ecodry pro 30

- 30 and 50 litres/day professional dehumidifiers
- Very compact modern styling, made from pearl white hi-gloss ABS
- Quiet and functional, with electronic control panel, display, humidistat and LEDs indicating operating status
- Condensation collection reservoir at the front with transparent window for viewing condensation level
- Hydraulic connection for continuous condensation drainage
- Rotary compressor
- Environmentally friendly refrigerant R410A

Dimensions: 540x340x252 mm (Ecodry pro 30)

Dimensions: 600x388x282 mm (Ecodry pro 50)

Humidifier and fragrance diffuser

STEAMY

- Compact and easy to use, can be fitted anywhere
- Produces cold mist at a consumption level of just 16 W
- Equipped with a special tray for essential oils
- 3 coloured LEDs indicate operating status
- Automatic shutdown if there is no water left
- Adjustable mist volume (+/- 20%)
- Independent operation of up to 3 hours without water refilling

Dimensions: 135xø167 mm

ml/h 100 **ml 350**

Humidifier

HYDRO digit

- Digitally-controlled ultrasound humidifier
- Produces cold or lukewarm mist at a very low energy consumption level
- Digital control panel with desired relative humidity level and mist emission level selection (high/medium/low)
- Programmable timer
- Built-in digital hygrometer for adjusting the ultrasound element
- Preheating function for even more effective humidification: the mist is lukewarm and the room temperature is therefore not lowered
- 360° adjustable mist emission
- Ion exchange filter that removes salts from the mist, to prevent them from being deposited in the room

Dimensions: 204x185x340 mm

ml/h 250 **ml 4000**

Purifier

PURO

- Personal air purifier
- Ideal for small rooms, individual offices, small workspaces, etc...
- Extremely quiet operation at a very low energy consumption level
- Makes use of electrostatic trap technology, which offers the advantage of not having to replace the filter
- Can be cleaned by removing the electrostatic trap and washing the elements with water and detergent
- Effectively eliminates bad odours
- Compliant with ARB standards, contributes to the elimination of numerous organic pollutants and bacteria

Dimensions: 330x120x81 mm

m^3 /h 18

JONIO professional

- Professional air purifier suitable for all applications, offices, large spaces, waiting rooms and also domestic environments
- High volume of treated air with low ventilation noise and reduced energy consumption
- Uses multi-layer purification technology, with HEPA filter and activated charcoal filter combined with activated titanium dioxide technology and ionisation
- Equipped with a self-cleaning function, maintenance consists solely of mechanical filter replacement
- Equipped with practical electronic controls and a remote control, it is easy to use and effectively eliminates pollen, synthetic and industrial pollutants, various atmospheric pollutants and bad odours, and contributes to the elimination of numerous organic pollutants and bacteria

Dimensions: 505x410x193 mm

m^3 /h 210

JONIO design

- Domestic air purifier, ideal for homes and offices
- Quiet, with very low energy consumption
- Uses HEPA filter technology and is able to remove up to 99.997% of particles up to a size of PM3 (3 microns) from the air
- Equipped with an additional ionisation function, it effectively eliminates pollen, synthetic and industrial pollutants, various atmospheric pollutants and bad odours
- Contributes to the elimination of numerous organic pollutants and bacteria

Dimensions: 495x363x167 mm

m^3 /h 210

JONIO easy

- Personal air purifier
- Ideal for small rooms, individual offices, small workspaces, etc...
- Extremely quiet operation at a very low energy consumption level
- Uses titanium dioxide technology to purify the air via the oxidation process
- Effectively neutralises bad odours and contributes to the elimination of numerous organic pollutants and bacteria

Dimensions: 243x85x98 mm

m^3 /h 10

Electric blankets, pillows and footwarmers

improve your life

Electric blanket

Daily

- Soft coral fleece blanket in anthracite grey, with luxury tone-on-tone detailing
- This extremely versatile product offers a warming embrace at any time of day: it can be used as a blanket on the sofa or in the armchair, or as an extra bed covering
- 5 power control settings
- Timer from 1 to 8 hours
- Overheating and short-circuit protection
- Power cable can be removed using the special connector with gold-plated contacts
- Machine washable at 40°C max.
- Compliant with European safety standards

Dimensions: 180x130 cm

W 120

Heated pillow

Warmy PAD

- Heated pillow with soft polar fleece covering
- Ultra-thin, ultra-light and contoured, it adapts perfectly to the body
- Warms and relaxes
- Removable outer cover, machine washable at 40°C max.
- 3 temperature control settings with indicator light
- Overheating and short-circuit protection
- Compliant with European safety standards

Dimensions: 40x32 cm

W 60

Electric footwarmer

QUCCI MASSAGE

- Soft electric footwarmer with built-in foot massager
- Ideal for warming cold feet, or for a relaxing massage to bring some welcome wellbeing to tired feet, or for an energetic massage to add a touch of vitality
- Outer cover in cotton and removable inner lining in soft wool, which is also machine washable at 40°C max.
- 2 temperature control settings from 30 to 55°C)
- 2 massage intensity levels (relaxing (1) and invigorating (2))
- Overheating and short-circuit protection
- Intelligent control for constant maintenance of the selected temperature

Dimensions: 33x28x13 cm **W 16**

Electric blankets

- Electric blankets with luxury detailing and rings for securing to the mattress
- Suitable for continuous use, to be placed between the mattress and sheet
- ARMONY has a dual purpose: it can be used as a fleece blanket without a power supply on sofas and, with a power supply, as an electric underblanket to be placed between the mattress and sheet
- Available in double (190x180) and single (180x90) versions
- Two power settings with short-circuit protection and automatic power cut-off
- The double version has two independently heated areas, for a maximum power of 60 watts per area
- Removable power cables with gold-plated connector contacts
- Hand washable (NATURE) or machine washable at low temperatures (ARMONY and SYNTONY)
- Compliant with European safety standards

Dimensions: 180x90 cm (Single) **W 60**

Dimensions: 190x180 cm (Double) **W 60+60**

Nature
PURE WOOL

Armony
COLOURED FLEECE

Syntony
POLYESTER

Essential oil diffusers
Mist lamps
Essential oil vaporisers

improve your life

Pure essential oil vaporisers

Oilo

- Three variants: white ceramic, black ceramic and silver plated
- Simple and safe, it diffuses the scent of essential oils by means of the heat produced inside it; however, the outer casing remains cool to the touch
- Do not use hot water: only pure essential oils or pure essential oil mixes
- Simply connect the power supply, flick the switch on and put a few drops of your favourite oil in the special essential oil compartment
- Can operate constantly in complete safety, because it is fitted with an overheating protection device, consuming just 5 watts
- A blue LED indicates its operation and creates a point of light if left running in the evening

Dimensions: 60xø130 mm

Fragrance diffuser

ZENO

- Essential oil diffuser with nebuliser and RGB LED bulb
- Ideal for small rooms, studies and for diffusing your favourite essential oils to create a relaxing environment almost anywhere
- The RGB LED bulb features continuously changing pastel coloured light that is pleasant and attractive to watch
- The colour of the light can be selected according to personal preference and the lamp can also be switched off to leave only the essential oil diffuser and vaporiser on
- Zeno is compact and adapts easily to any environment, it offers very low energy consumption and is made from plastic that is very pleasant to the touch. The base is available in two colours: white and pink

Dimensions: 150X128 mm

ml/h 15

LED RGB

- Mist lamps with RGB LED and all types of essential oil diffusers
- Ideal decorative furnishing accessories, these welcoming and attractive lamps produce an intense cold mist coloured by continuously changing pastel shades
- In the case of Aiko, the mist is dispersed throughout the room, while in Loto and Bamboo, the mist is contained within a glass bowl
- The relaxing action of the RGB lamp and the mist is further enhanced by the gentle sound of Japanese fountains, a distinguishing feature of the Bamboo product
- With the addition of your favourite essential oil and the natural production of anions, these lamps have a relaxing and reinvigorating effect
- Made using soft white frosted glass, they blend seamlessly into any room and decorative style

Dimensions: 189X ø 200 mm (Bamboo)
Dimensions: 180X ø 130 mm (Aiko)
Dimensions: 123X ø 130 mm (Loto)

ml/h ≥250

LED RGB

Technical specifications

Technical specifications

Fan heaters		**HI-FAN HiFi**	**HI-FAN Tower**	**HI-FAN Black Mini**	**HI-FAN Black Swing**	**HI-FAN Black**	**HI-FAN Classic**	**HI-FAN Digit**	**HI-FAN Digit plus**
Heat output	W	1500/2500	1300/2500	800/1200	1000/1800	1300/2000	900/1800	900/1800/auto	900/1800/auto
Heating volume	m^3	80	80	40	60	60	60	60	60
Portable unit		•	•	•	•	•	•	•	•
Wall-mounted fixed installation						•			
IP21 protection for use in bathrooms						•	•	•	•
Washable antibacterial/antimould filter		•	•	•		•			
Automatic rotation		•	•					•	•
Manual rotation						•	•		
Adjustable angle					•				
Summertime ventilation					•		•	•	•
Operating modes	no.	2	2	2	3	2	3	4	4
Manual thermostat					•		•		
Digital thermostat						•		•	•
Digital timer		•	•			•			
Programmable timer								•	•
Infrared remote control		•	•			•			•
Capacitive sensor controls		•	•			•			
Membrane-covered controls								•	•
LCD display		•	•			•		•	•
Forced ventilation		•	•	•	•	•	•	•	•
Tangential fan		•	•						•
Axial fan				•	•	•	•	•	
Ceramic heating element		•	•	•	•	•	•	•	•
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Power uptake	W	1500/2500	1300/2500	800/1200	1000/1800	1300/2000	900/1800	900/1800	900/1800
PTC protection		•	•	•	•	•	•	•	•
Overheating prevention device		•	•	•	•	•	•	•	•
Overturn prevention device		•	•	•		•	•	•	•
Dimensions (H./W./D.)	mm	1018/290/290	788/263/263	170/200/94	250/250/130	180/440/80	250/190/155	250/190/155	380/180/160
Weight	kg	5.6	4.7	1.2	1.75	2	1.6	1.6	2.1

Technical specifications

Fan heaters and multi-functional devices		**SPLITTO**	**SPLITTO Jr**	**QUADRO Black**	**ALIENO**	**UFO**	**ASTRO**
Heat output	W	1000/2000	1000/2000	1000/2000	1000/2000	1500	1000/2000
Heating volume	m^3	60	60	60	60	50	60
Portable unit				•	•	•	•
Wall-mounted fixed installation		•	•				
Humidification by cold evaporation				•			
Ionisation		•		•			
Dust and pollen filter				•			
Anti-freeze function							•
Summertime ventilation		•	•	•	•	•	•
Operating modes	no.	3	3	5	3	2	3
Manual thermostat							•
Digital thermostat		•		•			
Digital timer		•					
Programmable timer		•		•			
Infrared remote control		•					
Membrane-covered controls		•		•			
Button controls			•				
LCD display		•					
Forced ventilation		•	•	•	•	•	•
Manually adjustable deflectors				•			
Automatic deflectors		•	•				
Tangential fan		•	•				
Axial fan					•	•	•
Radial fan				•			
Ceramic heating element		•	•	•			
Wire-wound heating element					•	•	•
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Power uptake	W	1000/2000	1000/2000	1000/2000	1000/2000	1500	1000/2000
PTC protection		•	•	•			
Overheating prevention device		•	•	•	•	•	•
Overturn prevention device				•	•		•
Dimensions (H./W./D.)	mm	125/545/215	200/500/140	430/450/175	221/222/151	21.5(Diam.)/18.5(D.)	221/222/151
Weight	kg	3.5	3.2	5.5	1.1	1	1.1

Technical specifications

Fan heaters and radiant panel heaters		**HI FLOOR Design**	**HI FLOOR Design Plus**	**HI FLOOR Junior**	**HI FLOOR Classic**	**HI FLOOR Clas-sic T**	**HI FLOOR Ray**
Heat output	W	750/1250/2000	750/1250/2000	750/1250/2000	1000/2000	1000/2000	500/1000/1500
Heating volume	m^3	60	60	60	60	60	50
Portable unit		•	•	•	•	•	•
Wall mounting option							•
Manual thermostat		•	•	•	•	•	•
Manual timer			•			•	•
Button controls							•
Heating type		Convection	Convection	Convection	Convection	Convection	Radiation
Forced ventilation		•	•	•	•	•	
Modes/Power levels	no.	4	4	4	3	3	3
Axial fan		•	•	•	•	•	
Heating element type		wire	wire	wire	wire	wire	mica
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Power uptake	W	750/1250/2000	750/1250/2000	750/1250/2000	1000/2000	1000/2000	500/1000/1500
Overheating prevention device		•	•	•	•	•	•
Dimensions (H./W./D.)	mm	450/693/190	450/693/190	485/690/200	425/625/215	425/625/215	455/780/240
Dimensions (H./W./D.) without mounts	mm						455/780/80
Weight	kg	4.5	4.5	4.3	3.15	3.30	4.8

Mineral oil-filled electric radiators		**PEPPER 7**	**PEPPER 9**	**PEPPER 11**	**CHILY 7**	**CHILY 9**	**CHILY 11**
Heat output	W	600/900/1500	800/1200/2000	1000/1500/2500	900/1500	900/1500	1200/2000
Heating volume	m^3	51	60	60	42	51	60
Portable unit		•	•	•	•	•	•
Manual thermostat		•	•	•			
Button controls		•	•	•			
Heating via convection and radiation		•	•	•	•	•	•
Tubular heating element		•	•	•	•	•	•
Mineral oil-filled heating elements	no.	7	9	11	7	9	11
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Power uptake	W	600/900/1500	800/1200/2000	1000/1500/2500	900/1500	900/1500	1200/2000
Overheating prevention device		•	•	•	•	•	•
Overturn prevention device		•	•	•	•	•	•
Dimensions (H./W./D.)	mm	630/380/160	630/470/160	630/540/160	642/346/125	642/426/125	642/506/125
Weight	kg	10.2	11.9	13.3	8.04	10	11.96

Halogen and quartz heaters		**CALORELLA 1200 S**	**CALDOFAI 1200GR**	**CREOLA Q3**
Heat output	W	400/800/1200	400/800/1200	500/1000/1500
Heating volume	m^3	40	40	20
Portable unit		•	•	•
Radiated heat		•	•	•
Halogen bulbs	no.	3	3	
Quartz bulbs	no.			3
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50
Power uptake	W	400/800/1200	400/800/1200	500/1000/1500
Overheating prevention device		•	•	
Overturn prevention device		•	•	•
Dimensions (H./W./D.)	mm	500/310/225	550/400/300	210/410/183
Weight	kg	2.1	3.4	1.53

Technical specifications

Catalytic and infrared heaters ***Balanced flow gas radiators***		**44RQ**	**INFRA 42C**	**LYRA 4000 VTQ**	**LYRA 3000 VTQ**	**LYRA 3000 SQ**
Heat output	W	2270/2600/3050	1200/2800/4000	4000	3060	3060
Maximum heating capacity	W					
Max. heating volume	m^3	95	120	150	110	100
Portable unit		•	•	•	•	•
Flue pipe diameter	mm			120	120	120
Piezoelectric ignition		•	•	•	•	•
Pilot flame		•	•			
Manual heat output adjustment		•	•			
Thermostat modulating the flow of gas to the burner				•	•	•
Airtight combustion chamber in cast iron				•	•	•
Heating type		Radiation	Radiation	Convection	Convection	Convection
Forced ventilation				•	•	
Tangential fan				•	•	
Fan speeds	no.			1	1	
Methane gas consumption	m^3/h			0.400	0.310	0.310
LPG consumption	g/h	142/177/210	98/195/292	289	222	222
Power supply voltage	V/F/Hz			230/1/50	230/1/50	230/1/50
Carbon dioxide monitoring device		•	•			
Device protecting the pilot flame from being extinguished			•			
Overturn protection device			•			
Dimensions (H./W./D.)	mm	805/425/445	740/420/360	490/710/205	490/590/205	490/590/205
Weight	kg	18	9	40	30	30

Gas heaters		**VENTOSOLE 316 ASQ-A**	**VENTOSOLE 246 ASQ**	**THERMOSOLE 2.98 ASQ**	**THERMOSOLE 2.78 ASQ**	**THERMOSOLE 1.62 ASQ**
Heat output	W	9100	8500	7600	6900	5300
Maximum heating capacity	W	11000	10300	9200	8450	6500
Max. heating volume	m^3	400	380	270	250	200
Fixed wall/floor installation		•	•	•	•	•
Porcelain enamel paint fired at 900°C		•	•	•	•	•
Flue pipe diameter	mm	80/100	80	80	80	80
Electronic ignition		•				
Piezoelectric ignition			•	•	•	•
Pilot flame			•	•	•	•
Manual power adjustment						•
Thermostat modulating the flow of gas		•	•	•	•	
Forced ventilation		•	•			
Fan speeds	no.	2	1			
Methane gas consumption	m^3/h	1.164	1.090	0.940	0.860	0.690
LPG consumption	g/h	697	641	630	610	497
Power supply voltage	V/F/Hz	230/1/50	230/1/50			
Fume discharge monitoring device		•	•	•	•	•
Dimensions (H./W./D.)	mm	695/830/270	760/720/250	710/660/240	645/600/240	580/440/240
Weight	kg	38	35	27	23	13

Technical specifications

Pellet and wood-burning stoves		**MIGNON SL (green/grey)**	**SUPER SL (green/grey)**	**BRUCIAPELLET 65**	**BRUCIAPELLET 80**	**BRUCIAPELLET 110**
Heat output	W	6000	8000	7200	9400	13900
Max. heating volume	m^3	150	250	150	200	280
Heat output (min./max.)	kW			3.5 / 6.0	4.3 / 8.0	4.3 / 11.0
Output (min./max. power)	%			91 / 86	90 / 88.5	79 / 82
Surface area of hot plates	m^2	0.95	1.15			
Fixed floor installation		•	•	•	•	•
Porcelain enamel paint fired at 900°C		•	•			
Flue pipe diameter	mm	100	120	80	80	80
Wood consumption per 24 hours	kg	6 / 8	10 / 12			
Output of wood-burning stove	%	70.5	70			
Wood-burning combustion chamber volume	dm^3	16	24			
Stainless-steel brazier				•	•	•
Electronic ignition				•	•	•
Electronic adjustment of heat output				•	•	•
Electronic room temperature regulation				•	•	•
Programmed ignition management day/week (2 progr./day)				•	•	•
Digital display				•	•	•
Optional remote control				•	•	•
Radiated heat		•	•			
Heating via forced ventilation				•	•	•
Pellet consumption (min./max. power)	kg/h			0.7 / 1.4	0.9 / 1.78	1.03 / 2.65
Reservoir capacity	kg			13.5	15	15
CO2 values (at 13% of O2) (min./max. power)	%			0.040 / 0.018	0.018/ 0.021	0.028 / 0.013
Power uptake on ignition	W			380	300	300
Power uptake during operation	W			100	100	100
Power supply voltage	V/F/Hz			230/1/50	230/1/50	230/1/50
Dimensions (H./W./D.)	mm	740/320/320	860/380/380	930/460/510	1040/520/550	1040/520/550
Weight	kg	49	75	80	119	119

Dehumidifiers		**ECODRYPRO 30**	**ECODRYPRO 50**	**POWERDRY 13**	**POWERDRY 17**
Dehumidification capacity	l/day	30	50	13	17
Reference temperature		30°	30°	32°	32°
Reference relative humidity		80%	80%	80%	80%
Max. air flow rate	m^3/h	230	312	115	126
Tank/reservoir capacity	l	5	6.6	2.5	2.5
Sound pressure	dB(A)	44	48	40	40
Portable unit		•	•	•	•
Manual humidistat				•	•
Electronic humidistat		•	•		
Anti-mould and anti-pollen filter and mesh		•	•	•	•
Digital timer		•	•		
LCD display		•	•		
Fan speeds	no.	2	2	1	1
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50
Power uptake	W	520	740	260	410
Dimensions (H./W./D.)	mm	540/340/252	600/388/282	490/365/220	490/365/220
Weight	kg	13.2	19.5	11.2	13.3

Technical specifications

Dehumidifiers		**NARCISO Baby10**	**NARCISO 12**	**NARCISO 16**	**NARCISO 20**	**NARCISO 24**
Dehumidification capacity	l/day	10	12	16	20	24
Reference temperature		30°	30°	30°	30°	32°
Reference relative humidity		80%	80%	80%	80%	80%
Max. air flow rate	m^3/h	90	150	180	180	180
Tank/reservoir capacity	l	1.8	3.5	3.5	3.5	3.5
Sound pressure	dB(A)	38	41	42	42	42
Portable unit		•	•	•	•	•
Manual humidistat		•	•	•	•	•
Anti-mould and anti-pollen filter and mesh		•	•	•	•	•
Fan speeds	no.	1	1	1	1	1
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Power uptake	W	185	260	320	320	340
Dimensions (H./W./D.)	mm	435/321/258	632/405/290	632/405/290	632/405/290	632/405/290
Weight	kg	10.6	13.5	13.8	14	14

Humidifiers and purifiers		**STEAMMY**	**HYDRO DIGIT**	**PURO**	**JONIO PROFESSIONAL**	**JONIO DESIGN**	**JONIO EASY**
Max. air flow rate	m^3/h			18	210	210	10
Tank/reservoir capacity	l	0.35	4				
Sound pressure	dB(A)			<20	45	30	15
Portable unit		•	•	•	•	•	•
Max. output ml/h		100	250				
Max. room volume	m^3	40	60	40	110	110	40
Manual humidistat		•					
Ultrasound humidification		•	•				
Electronic humidistat			•				
Anti-mould and anti-pollen filter and mesh					•	•	
Activated charcoal filter					•	•	
HEPA filter					•	•	
Vegetable fibre catalytic filter						•	
Photocatalytic filter							•
Self-regenerating photocatalytic filter					•		
Ion exchange filter		•	•				
Electrostatic filter				•			
Ionisation		•	•		•	•	•
Compliant with ARB standards				•			
Programmable timer		•	•		•	•	
Infrared remote control					•	•	
Membrane-covered controls					•		
Button controls		•	•	•		•	•
LCD display			•			•	
Transformer		24 V					
Fan speeds	no.	1		1	3	3	
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
Power uptake	W	16	85	2.8	70	40	5
Dimensions (H./W./D.)	mm	135(H.)/ ø167	204/185/340	330/120/81	505/410/193	495/363/167	243/85/98
Weight	kg	0.65	2.5	1	6.7	4.5	0.56

Technical specifications

Electric blankets, pillows and footwarmers		**DAILY**	**WARMY Pad**	**QUCCY Massage**	**NATURE Single**	**NATURE Double**	**ARMONY Single**	**ARMONY Double**	**SINTONY Single**	**SINTONY Double**
Blanket for single bed					•		•		•	
Blanket for double bed						•		•		•
To be placed between the mattress and sheet					•	•	•	•	•	•
Top blanket for bed or sofa		•								
Heated pillow with fleece cover			•							
Footwarmer with wool inner lining				•						
Pure Australian wool					•	•				
Polar fleece			•(outer fleece)				•	•		
Soft polar fleece		•								
Polyester									•	•
Colour		anthracite	blue	brown	white	white	blue/fuchsia	blue/fuchsia	white	white
Rings for securing the blanket to the mattress					•	•	•	•	•	•
Independent areas	no.				1	2	1	2	1	2
Adjustable vibration levels				2						
Removable power cable		•	•		•	•	•	•	•	•
Connectors with gold-plated contacts		•			•	•	•	•	•	•
Hand washable					•	•				
Machine washable on delicates cycle, max. temp. 40°		•	•(outer fleece)	•(inner)			•	•	•	•
PVC inner, not washable			•							
Protection against overheating		•	•	•	•	•	•	•	•	•
Protection against short circuits		•	•	•	•	•	•	•	•	•
Control transformer				DC12V						
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Dimensions (H./W./D.)	cm	180/130	400/320	33/28/13	180/90	190/180	180/90	190/180	180/90	190/180
Weight	kg	1.75	0.45	0.85	1.81	3.8	1.26	2.7	1.16	2.34

Technical specifications

Diffusers, essential oil vaporisers and mist lamps		**OILO**	**ZENO**	**BAMBOO**	**AIKO**	**LOTO**
Essential oil diffuser			•			
Pure essential oil vaporiser		•				
Decorative lamp and essential oil diffuser				•	•	•
Nebuliser with built-in RGB LED bulb			•	•	•	•
Base made from special white plastic			•			
Base made from special pink plastic			•			
Frosted white glass				•	•	•
Bamboo base				•		
White - black - silver-plated ceramic		•				
Water fountain sound playback				•		
Ultrasound humidification			•	•	•	•
Continuous colour variation			•	•	•	•
Option to stop on a chosen colour			•			
Mist emission into the room			•		•	
Mist emission inside the sphere				•		•
Reservoir capacity	ml		80	1600	800	1200
Volume of mist emitted	ml/h		15±5	≥250	≥250	≥250
Power supply voltage	V/F/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Transformer			DC24V	AC24V	DC24V	DC24V
Power uptake	W	5	12	24	15	15
Dimensions (H.-C.)	mm		150/128			
Dimensions (H./D.)	mm	60/ø130			180/ø130	123/ø130
Sphere dimensions (H./D.)	mm			189/ø200		
Dimensions of Bamboo base (H./W./D.)	mm			54/210/170		
Weight	kg	0.55	0.4	2.2	1	1.5

www.argoclima.com

702011206 - 07/11

improve your life

argoclima S.p.A.

Head office
Via Varese, 90
21013 Gallarate (VA) ITALY
Tel: + 39 0331 755111
Fax: + 39 0331 776240
www.argoclima.com

N.B. The manufacturer assumes no responsibility for any errors or inaccuracies in the content of this catalogue, and reserves the right to make any necessary changes to its products, at any time and without notice, for technical or commercial reasons.

www.orangetown.com

Argo is a **argoclima S.p.A.** brand, a leading European company in Climate control, Heating and Air treatment.